

ALPHA 9000 SERIES - 9020W



P2 DISPOSABLE RESPIRATOR

A traditional range of lightweight cup shape respirators offering excellent value.

KEY FEATURES

- Range tested to 'Dolomite Clogging Test (D)'
- Full inner face seal
- Traditional metal nose clip adjustment
- Soft, lightweight fabrics
- Exhalation valve that reduces temperature and humidity build-up and improved exhalation resistance
- Pre-filter with activated carbon to protect against nuisance odours and organic vapours below the WEL
- Conforms to EN149 : 2001 + A1 : 2009



ORDERING INFORMATION

Part Number: 9020W

Packaging: 5 singles per box
12 boxes per case

Certification: EN149: 2001 + A1 : 2009
FFP2 NR D

SUITABLE APPLICATIONS

Protects from non-toxic dust and oil/water based particulates. Some suitable applications include:

- **Craft Work**
- **Cutting & Casting of Metals**
- **Hospital**
- **Iron & Steel Industry**
- **Laboratory & Disease Control**
- **Mining**
- **Textile Industry**
- **Underground Civil Engineering**
- **Welding work**
- **Woodworking**

ALPHA 9000 SERIES - 9020W



P2 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL
Outer Layer:	Polypropylene Fabric
Filter Media:	High Filtration Efficiency Melt-Blown (Polypropylene)
Inner Layer:	Polyester Fabric
CV Pre-filter:	Active Carbon with Polypropylene Substrate
Nosebridge:	Aluminium
Nosefoam:	PVC Foam
Headstrap:	Knitted Elastic Band
Headstrap Buckle:	Polypropylene (PP)
Exhalation Valve:	Valve Housing – Polypropylene Valve Membrane – Synthetic Rubber

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
Respirator:	139	127	54
Nosebridge:	90	5	0.5
Nosefoam:	139	127	2
Headstrap Upper:	540	10.5	1.5
Headstrap Lower:	460	10.5	1.5
Exhalation Valve:	41 (Diameter)	-	11

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands. [N.B. No.2797].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

Approval EN 149:2001 + A1:2009	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	Odours / Org. Vapours (Below WEL)	VeryFine / Toxic Dusts / Mists / Fumes	Metal Fumes	Oil/Water Based Particulates
FFP1 NR D	9010	4	■					■
FFP1 NR D	9010V	4	■					■
FFP2 NR D	9020	10	○	■			○	■
FFP2 NR D	9020V	10	○	■			○	■
FFP2 NR D	9020W	10	○	■	■		■	■
FFP3 NR	9030V	20	○	■		■	■	■

■ = Recommended ○ = Alternative

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Alpha Solway Ltd

Part of
Globus
GROUP