

ALPHA 9000 SERIES - 9020V



P2 DISPOSABLE RESPIRATOR

A traditional range of lightweight cup shape respirators offering excellent value.

KEY FEATURES

- Range tested to 'Dolomite Clogging Test (D)'
- Soft inner nose seal
- Traditional metal nose clip adjustment
- Soft, lightweight fabrics
- Low profile valve reduces exhalation resistance keeping the wearer cooler
- Conforms to EN149: 2001 + A1: 2009



ORDERING INFORMATION

Part Number: 9020V

Packaging: 10 singles per box
12 boxes per case

Certification: EN149: 2001 + A1: 2009
FFP2 NR D

SUITABLE APPLICATIONS

Protects from non-toxic dust and oil/water based particulates. Some suitable applications include:

- **Craft Work**
- **Cutting & Casting of Metals**
- **Hospital**
- **Iron & Steel Industry**
- **Laboratory & Disease Control**
- **Mining**
- **Textile Industry**
- **Underground Civil Engineering**
- **Welding work**
- **Woodworking**

ALPHA 9000 SERIES - 9020V



P2 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

| COMPONENT | MATERIAL |
|--------------------------|--|
| Outer Cover: | Polypropylene Fabric |
| Filter Media: | High Filtration Efficiency Melt-Blown (Polypropylene) |
| Inner Cover: | Polyester Fabric |
| Headstrap: | Latex-Free Synthetic Rubber |
| Nosebridge: | Aluminium |
| Nosefoam: | Polyethylene [PE] Foam |
| Exhalation Valve: | Valve Housing – Polypropylene Valve Membrane – Synthetic Rubber |

DIMENSIONS

| ITEM | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) |
|--------------------------|------------------|------------|-------------|
| Respirator: | 139 | 127 | 54 |
| Nosebridge: | 90 | 5 | 0.5 |
| Nosefoam: | 100 | 27 | 1.5 |
| Headstrap Upper: | 300 | 5 | 0.55 |
| Headstrap Lower: | 265 | 5 | 0.55 |
| Exhalation Valve: | 41 (Diameter) | - | 11 |

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands. [N.B. No.2797].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

| Approval EN 149:2001 + A1:2009 | Product Codes | APF (Assigned Protection Factor) (x WEL) | Non-Toxic Dusts | Fine / Toxic Dusts / Mists / Fumes | Odours / Org. Vapours (Below WEL) | VeryFine / Toxic Dusts / Mists / Fumes | Metal Fumes | Oil/Water Based Particulates |
|--------------------------------------|------------------|--|--------------------|---|---|---|----------------|------------------------------------|
| FFP1 NR D | 9010 | 4 | ■ | | | | | ■ |
| FFP1 NR D | 9010V | 4 | ■ | | | | | ■ |
| FFP2 NR D | 9020 | 10 | ○ | ■ | | | ○ | ■ |
| FFP2 NR D | 9020V | 10 | ○ | ■ | | | ○ | ■ |
| FFP2 NR D | 9020W | 10 | ○ | ■ | ■ | | ■ | ■ |
| FFP3 NR | 9030V | 20 | ○ | ■ | | ■ | ■ | ■ |

■ = Recommended ○ = Alternative

www.alphasolway.com T: +44 (0)1461 202452 E: alphasolway.sales@globusgroup.com

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Alpha Solway Ltd

Part of
Globus
GROUP