

EXTENDED PROTECTION FROM HAND TO SHOULDER

Resistant to chemicals, oils and acids while offering full protection from the fingers up to the shoulder. Long sleeve version of the SHOWA 771.

FEATURES

- › Glove and sleeve are integrated
- › Full protection from fingers up to shoulder
- › Liner of the sleeve is thinner and softer than the glove, so does not affect operability
- › Rough surface on glove enhances grip and durability
- › Elasticated seal for a secure fit
- › Anti-bacterial treatment (interior)
- › Ventilation eyelet
- › Thickness: 0.8mm
- › Length: 65cm



SUITABLE FOR


Typical Industries

- Chemical
- Construction
- Engineering
- Oil and Gas

Suitable Applications

- Drilling and Boring
- Engine Servicing
- Janitorial
- Packing of Chemical Substances

CERTIFICATION



See overleaf for explanation

PRODUCT INFORMATION

| | | |
|--------------------|-------------------------------|---------|
| MATERIALS | LINER: | Cotton |
| | COATING: | Nitrile |
| COLOUR | Yellow | |
| LENGTH (mm) | 650 | |
| CUFF STYLE | Gauntlet with extended sleeve | |

ORDERING DETAILS

| SIZE | CODE | PACKAGING |
|-------|---------|--------------------------------------|
| 8/M | SHO7722 | 5 pairs per bag 60 pairs per case |
| 9/L | SHO7723 | |
| 10/XL | SHO7724 | |

RECOMMENDATIONS FOR USE

- **USE:** Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604:2004 (method B)



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

| CODE | CHEMICAL | CODE | CHEMICAL | TYPE OF GLOVES | BREAKTHROUGH TIME |
|------|------------------|------|------------------------|----------------|----------------------------------|
| A | Methanol | J | n-Heptane | A | ≥30 min for at least 6 chemicals |
| B | Acetone | K | Sodium hydroxide 40% | | |
| C | Acetonitrile | L | Sulphuric acid 96% | B | ≥30 min for at least 3 chemicals |
| D | Dichloromethane | M | 65% Nitric acid | | |
| E | Carbon Disulfide | N | 99% Acetic acid | C | ≥10 min for at least 1 chemical |
| F | Toluene | O | 25% Ammonium hydroxide | | |
| G | Diethylamine | P | 30% Hydrogen peroxide | | |
| H | Tetrahydrofuran | S | 40% Hydrofluoric acid | | |
| I | Ethyl acetate | T | 37% Formaldehyde | | |

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2020 Globus (Shetland) Ltd | SHO-DATA-772_0620_1