

360 DEGREE CUT AND CHEMICAL RESISTANT PVC IMPACT GAUNTLET

This PVC impact gauntlet features surprisingly responsive impact protection without sacrificing grip or chemical protection.

FEATURES

- › Cut resistance : Level D (EN388:2016) / ANSI A4
- › PVC provides excellent protection against water, mud, oils, hydrocarbons and corrosive chemicals
- › Sandy coated palm ensures grip in dry, wet, oily and chemical handling applications
- › Ergonomically curved fingers to reduce hand fatigue
- › Cushioned impact coverage balances dexterity with protection
- › 350mm length for extended cuff protection
- › ANSI Level 2 impact coverage



SUITABLE FOR

Typical Industries

- Oil and Gas
- Mining
- Transport
- Heavy Engineering
- Offshore
- Ports
- Construction

Suitable Applications

- Fueling
- Drilling
- Fishing
- Cementing

CERTIFICATION

CAT III	EN 388:2016	EN ISO 374-1:2016/Type A	EN ISO 374-5:2016	ASTM / ANSI 105-2016
0598	4X42DP	AKLMPT	Virus	CUT
ANSI / ISEA 138				

See overleaf for explanation

MATERIALS

MATERIALS	DIPPING:	PVC
	LINER:	Cut resistant fabric
COLOUR	Green	
LENGTH (mm)	350 (Size Dependent)	
CUFF STYLE	Gauntlet	

RECOMMENDATIONS FOR USE

- USE: Chemical, cut and impact resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement.
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight.
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SKG00023CF	6 pairs per bag
9/L	SKG00023CH	
10/XL	SKG00023CJ	
11/XXL	SKG00023CL	
12/XXXL	SKG00023CN	36 pairs per case

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

