

REINFORCED CUT RESISTANT GLOVE WITH A LEATHER PALM

The soft, supple leather palm provides good grip in wet and oily conditions. Excellent cut resistance with high levels of protection from abrasion and tearing.

FEATURES

- › Cut resistant: Level F (EN 388:2016)
- › Breathable back of hand to help reduce perspiration and skin irritation
- › Anti-bacterial treatment to reduce odours
- › Good grip in wet and oily conditions
- › Anatomically designed for comfort and fit
- › Para-aramid stitched for durability and strength
- › Elasticated wrist for a secure fit
- › Maximum resistance to abrasion and tearing
- › Seamless knitted liner prevents irritation



SUITABLE FOR

Typical Industries

- Automotive
- Glass
- Manufacturing
- Municipal Services
- Steel and Metal

Suitable Applications

- Glass Manufacture Including Soft Coat
- Injection Moulding
- Machine Shop Work
- Wet and Dry Glass Handling

CERTIFICATION



See overleaf for explanation

PRODUCT INFORMATION		
MATERIALS	LINER:	Aramid
	COATING:	Leather
COLOUR	Yellow/Grey	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE
<ul style="list-style-type: none"> USE: General handling glove with cut protection. Not suitable for high thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement STORAGE: Store in dry conditions in the original packaging and away from direct sunlight CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present. LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS		
SIZE	CODE	PACKAGING
8/M	SKY0222	10 pairs per bag
9/L	SKY0223	60 pairs per case
10/XL	SKY0224	

CERTIFICATION LEGENDS	
<p>MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*</p> <p>0-4 0-5 0-4 0-4 A-F P</p> <p>Abrasion Resistance Circular Blade Cut Resistance Tear Resistance Puncture Resistance Straight Blade Cut Resistance (EN ISO: 13997) Impact Resistance</p> <p>*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter</p>	<p>HEAT AND FIRE EN 407</p> <p>PERFORMANCE LEVELS</p> <p>0-4 0-4 0-4 0-4 0-4 0-4</p> <p>Contact Heat Resistance Convective Heat Resistance Radiant Heat Resistance Resistance to Small Drops Of Molten Metal Resistance to Large Splashes of Molten Metal Burning Behaviour</p>

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

